









## PRODUCT DESCRIPTION

Introducing our newest EZ Tube Display, the EZ Pillar! This display is very light-weight and is an excellent attention grabber due to its sheer size. The aluminum frame is completely tool free and easily assembled by snapping all of the individual tubes together. The graphic slides over the frame, pulled down until taut, and then is zipped closed. A durable case with wheels for easy transport is included. Grab all the attention at your next show with this massive display!

<b>DISPLAY DIMENSIONS</b>	36"W x 120"H x 36"D

GRAPHIC SIZE 56.128"W x 120"H (2 prints total)

## **GRAPHIC MATERIAL**

Multi-Stretch Fabric

### **GRAPHIC FINISHING**

Dye Sublimation with Pillowcase Finishing

### **DISPLAY CONSTRUCTION**

Aluminum Frame (38mm diameter tubing)

## SHIPPING WEIGHTS & DIMENSIONS

	25 lbs (stand only) 32 lbs (frame and graphic)
--	---

Shipping Dimensions 66.25"L x 12.5"W x 5"H

### LARGE QUANTITY FREIGHT

Freight Shipping	20 boxes per 48"L x 40"W x 31"H skid
Freight Weight	545 lbs (frame only)

ight Weight | 545 lbs (frame only) 685 lbs (frame & graphic)

## **GRAPHIC TURN AROUND TIME**

2 business days after proof approval

## AVAILABILITY CA



Silverbag Case






1.5" (38mm) dia. Frame Tubing




# **PARTS LIST**



Qty.8 - Vertical Sectional Tubing



Qty.8 - 1.75" Hardware w/ Allen Key



Qty.8 - Top and Bottom Sectional Tubing



Qty.1 - Silverbag

# SETUP INSTRUCTIONS

### A. Vertical Tubing





Push down on the button and insert into the receiving tube until the button snaps in place. Match the labels, located on the ends of every piece(ex:T1:T1,T4:T4,etc.).

## B. Top and Bottom Tubing




Assemble the top and bottom sections the same way as the vertical tubing. Push, insert, and snap. Match the labels found at each end.

## C. Attach Top and Bottom to Vertical Tubing





Attach the top and bottom sections to the vertical tubing, which screw into the ends of each vertical tube. Allen key is supplied.





## 1. Drape



Drape the top of the frame, starting with the open end (bottom) of the graphic.

## 2. Pull



Pull the graphic all the way down until taut.

### 3. Zip





Zip the bottom shut to maximize tension. The graphic install is complete.