











PRODUCT DESCRIPTION

The advanced technology of the new SEGO modular lightbox system combines innovation with intuition. Toolless down to its feet, SEGO is designed to help heighten your display experience. Magnetic electrical connectors light up the UL certified LED lights that come pre-installed in the profiles. Electrical wires stay hidden from view. Edge-to-edge customizable SEG backlit fabric graphics cover the front and back of the aluminum frame. Portable, configurable, desirable, SEGO is a lightbox unlike the others. SEGO is so well thought out, even its durable foam cut carry bag is made distinctly to keep all parts and pieces protected and organized.

DISPLAY DIMENSIONS	39"W x 39"H x 16.5"D
GRAPHIC SIZE	39.625"W x 39.75"H

GRAPHIC MATERIAL

Dye Sub Backlit Fabric

GRAPHIC FINISHING

Silicone beading sewn onto edge of graphic

DISPLAY CONSTRUCTION

Aluminum extrusion frame with plastic components

SHIPPING WEIGHTS & DIMENSIONS

Shipping Weight	21.5 lbs (frame only) 23 lbs (frame & graphic)
Shipping Dimensions	45.5"W x 15.5"H x 6.75"D

GRAPHIC TURN AROUND TIME

CERTIFICATES UL, CE, GEM VOLTAGE INPUT 100-240V VOLTAGE OUTPUT 24V

2 business days after proof approval (up to 6 sets)

AVAILABILITY CA

LED LIGHT SPECIFICATION		LUMENS		
BRAND	Osram	VOLTAGE (V)	24	
POWER	3W	POWER (W)	45	
CCT (COLOR TEMP)	6800k	LM/W	130	
AVERAGE BEAM ANGEL	20 °	TOTAL LM	5850	
LM/W	130	AVG LM	5850	
AVG LM/M ²	4800-5800	CU	.8	
VOLTAGE INPUT	24V	EAV	4680	
TRANSFORMER SPECIFI	CATION			
POWER RATE 2	95W, 252W			
TRANSFORMERS				











MAGNETIC WIRE CONNECTION





CLEAN CABLE MANAGEMENT




TOOL FREE FOOT CONNECTION


PARTS LIST






















AVAILABLE ACCESSORIES




SEGO-HLCON SEGO High-low Connector



SEGO-OLCON SEGO L Connector Outside



SEGO-SCON SEGO Straight Connector



SEGO L Connector Inside

SET UP INSTRUCTIONS

