WLM-SEAHORSE B – Straight Header



(3)

(3)

99

9

(f)

Setup Instructions

- 1. Take all the parts out of the bags and lay them on the ground according to the assembly diagram.
- 2. Make sure that all the corresponding numbers are correct.
- 3. Now start pushing the pipes together until they firmly click, if difficult you can slightly twist the parts together to make the locking spring pop up on place.
- 4. Its time to get your hands cleaned as now you are ready to handle the printed fabric. Feed the fabric from the round edges of the frame, feed only a few feet, then stand the frame up then slide the fabric to the bottom, now close the Zipper.

Media Cabl

Media Cable

Monitor

Monitor Cord

<u>2951mm(116,2")</u>

2259mm(88.9")

2658mm(104.6")

- 5. You can set up the feet in the position that you want to erect the stand, lift the fabric panels and fit on the feet.
- 6. To lock the frames together you can use the "S" shaped brackets, they are designed tight so they lock well.
- 7. If you have a header in the kit you can fix to the top by using the clear plastic clips.

	(22) (E2)	35	90°	10	05)	NO.
Frame	2	2	2	2	2	Quantity
						Confirm
	16	09	25) clear	23	37	NO.
Frame	2	2	4	2	_	Quantity Confirm
					34)	NO.
Frame					34 1	Quantity Confirm
						NO.
Frame						Quantity Confirm
			\			NO.
Frame						Quantity
Frame						NO. Quantity Confirm NO.
						Confirm
-	22.6"	32"	40"			
TV kit						Confirm
Shipp	CA900	CA500				NO.
ing Case						Confirm
Shipping Case accessories						